



178 mm slipmaskin m. Utsug

7" Dia. Disc Sander

1.3 hp, Right Angle Disc Sander

Unique Vacuum Shroud Captures Contaminants

- For use on non-ferrous surfaces such as Carbon Fiber, Composites, Fiberglass, Turbine Blades, more.
- Vacuum Shroud captures airborne contaminants such as Hexavalent Chromium.
- 1-1/4" diameter Swivel Cuff improves maneuverability.
- Vibration Dampening Side Handle (for left or right hand use).



Includes "View Port" for enhanced visibility!

Central Vacuum

Model 52597

6,000 RPM, 5/8"-11 Spindle Thread

- An essential tool for nuclear plants, aerospace, wind energy, automotive and marine markets.
- Tool accepts optional 7" (178 mm) diameter Abrasive Discs with 7/8" (22 mm) center hole.
- Includes 51151 Backing Pad, 7" (178 mm) in diameter, and flange (see below).
- Lightweight non-marring Vacuum Shroud is constructed of high-quality clear urethane.
- 3/4" (19 mm) Shroud Brush assists in capture of airborne contaminants.
- Includes Conductive Hose & Cuffs, to shield operator from electrostatic discharge (ESD).
- Shroud has "View Port" which allows operator to see abrasive disc and work surface.
- Quiet, robust 1.3 hp air motor is governor-controlled to maintain consistent RPM under load.
- Convenient Spindle Lock allows quick and easy changing of backing pad or abrasive.
- "Wick Lube" System extends gear life with regular lubrication.



Gear Oil & Gear Oil Gun

- Included with tool, and also sold separately.

95848 Gear Oil

- To lubricate Dynabrade tools with "Wick Lube" System, such as 52597 above.

95541 Push-Type Gear Oil Gun

- Easy one-hand operation.



Backing Pad

51151

- Thermoplastic pad with fins.
- 7" (178 mm) diameter.
- Accepts Abrasive Discs with 7/8" (22 mm) center hole.
- Fins help expel heat from disc pad, extending disc life.
- Flange nut included.



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Spindle Thread	Air Pressure PSIG (Bar)	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52597	1.3 (969)	6,000	76 dB(A)	40 (1,138)	5/8"-11 Male	90 (6.2)	5.8 (2.6)	14-5/8 (373)	3-7/8 (104)