

# SLANGUPPRULLARE TRYCKLUFT / EL

10-1014-1230



11-1318-1530



15-1014-1630



14-1320-1530



14-1318-1630



18-0812-1030  
19-1013-1530



12-1014-2530



13-0812-1230



Samtliga slangupprullare utrustade med svängbart väggfäste.

Slangens temperaturområde: -30 – +60°C

Slagkvalitet: Ultraflex PU

	Slang m	Slang Ø mm	Ansl. utv. G	Max tryck Bar	Ansl slang	Kapacitet l/min	Vikt Kg	Art.nr
<b>KAPSLAD KOMPOSIT</b>								
	10	8 x 12	1/4"	16	1	300	4,5	18-0812-1030
	15	9,5 x 13	1/4"	16	1	400	6,9	19-1013-1530
<b>KAPSLAD STÅL</b>								
	12	9,5 x 13	1/4"	20	1,5	400	9,0	10-1014-1230
<b>KAPSLAD STÅL</b>								
	15	13 x 18	1/2"	16	0	1250	20,0	11-1318-1530
<b>ÖPPEN STÅL</b>								
	16,5	10 x 14	1/4"	20	1,5	600	12,0	15-1014-1630
	15	10 x 17	3/8"	20	1,5	600	12,0	15-1017-1530*
*Material: Gummi. Passar till: luft/vatten								
<b>ÖPPEN STÅL</b>								
	16,5	13 x 18	3/8"	20	1,5	950	11,0	14-1318-1630
	15	13 x 20	1/2"	20	1,5	950	11,0	14-1320-1530*
*Material: Gummi. Passar till: luft/vatten								
<b>ÖPPEN STÅL</b>								
	25	10 x 14	1/4"	20	1,5	500	8,3	14-1014-2530
<b>KAPSLAD STÅL</b>								
	12	8 x 12	1/4"	12	0,5	400	9,0	13-0812-1230



BB-17-0315-1530

	Sladd m	Kabel	Max effekt	Ansl kabel	Kontakt	Vikt Kg	Art.nr
<b>KAPSLAD PLAST</b>							
	15	3 x 1,5	1000/2000	1	Schuco	6,5	17-0315-1530